Alphion

Product Brief

AMUX-7232

32/48-port GPON/XG(S)PON/Co-Existence PON OLT

Feature Summary

- 19" standard rack mountable 2RU Chassis
- Redundant Power
- Redundant Control & switch modules
- Hot-Swappable Modular design for Control & Switch modules, power-supplies and fans
- Supports maximum of two 16/24 GPON/XG(S)PON port line cards or two 8/16/24 XG(S)PON & GPON Combo port service cards
- PON Protection on XG(S)PON/GPON Ports (Class-B)
- Four 25G/10G/1G SFP28/SFP+/SFP uplink ports on each Control & Switch module

XG(S)PON & GPON Technology

- Complies with ITU-T G.984.1-5, G.987/G.988, G.9807 standards
- Supports 10 Gbps/2.5Gbps downstream & 10 Gbps/2.5Gbps/1.25Gbps upstream XG(S)PON/GPON Interfaces
- Supports 5 T-CONT types as per G.984.3 standards
- Supports SN/SN+Password ONU Authentication
- Supports Dynamic Bandwidth Allocation (DBA)
- Supports FEC and Rogue ONU detection

Switching and advanced features

- Supports line-speed switching and forwarding capabilities
- Supports 355K MAC address table
- Supports advanced L2 Switching features and VLAN functionality
- Supports IPv4/IPv6 DHCP Server / DHCP Relay functionality
- Supports IPV4 and IPV6 Multicasting
- Supports time-synchronization using PTP and SyncE
- Supports abundant QOS functions
- Supports advanced security features

Powering

Dual AC/Dual DC redundant power inputs, with pluggable AC and DC inputs modules.



Applications

The AMUX-7232 is 2RU Chassis based hybrid platform which supports GPON/XGPON/XGSPON functions and completes the end-to-end optical last mile with up to 10Gbps bandwidth for triple play services to residential and business customers The high subscriber density and low-cost of entry, combined with the operational cost-savings of GPON Technology, makes AMUX-7232 a compelling alternative to legacy last-mile solutions.

Standards

The AMUX-7232 design takes advantages of the latest switching technologies. By complying with the FSAN/ITU-T XG(S)PON and GPON standards, the AMUX-7232 achieves interoperability with a wide range of XG(S)PON and GPON ONTs. With PTP and SyncE support, the AMUX-7232 can be also used in mobile backhaul solutions.

Flexible Provisioning, Management and QOS

The AMUX-7232 supports Telnet/SNMP/CLI for remote management. Its powerful OMCI functions enable remote diagnostics and flexible provisioning of the ONU/ONTs. It's enriched QOS functions such as traffic policy/traffic shaping/rate limit/schedule allows operators to provide flexible bandwidth allocation policy for multiple customized services.

THIS PRODUCT BRIEF IS SUBJECT TO CHANGE AND IS PROVIDED ON AN "AS-IS" BASIS.

SPECIFICATIONS

XG(S)PON/GPON Interface

Ports:	Up to 48 XG(S)PON/GPON/Combo PON ports**
Standards:	ITU-T G.984, G.987/G.988, G.9807 compliant
Line rate:	GPON: 1.25Gbps (Upstream), 2.5Gbps (Downstream) XGPON: 2.5Gbps (Upstream), 10Gbps (Downstream) XGSPON: 10Gbps (Upstream), 10Gbps (Downstream)
Fiber Type:	Single-Mode, BIDI
Transceiver:	Supports B+/C+(GPON) and N1&B+/N2&C+/E2&D XG(S)PON&GPON Combo transceivers
Split ratio:	1:64 (GPON) and 1:128 (XG(S)PON)
Interface Type:	SC/UPC
Tx Power:	3~7dBm (C+), 4~8dBm (N2a)
Rx Sensitivity:	-30 dBm (C+), -29.5dBm (N2a)
Rx Overload:	-12 dBm (C+), -9dBm (N2a)
Wavelength:	GPON - Rx: 1310nm and Tx: 1490nm XG(S)PON - Rx: 1270 nm and Tx:1577nm
T-CONT:	1-5

Ethernet Uplink Trunking Interfaces

25GE/10GE/1GE:	Two cards of 4xSFP28/SFP+/SFP Ports

Timing Interfaces

SyncE	1xRJ45 Ethernet port

Management Interfaces

Out-Of-Band	1xRJ45 Ethernet port
Console	1xRJ45 COM port

Switching

Switching Capacity	960 Gbps
Throughput:	714 Mbps
VLAN Support:	Port based VLAN, Protocol based VLAN and 801.q VLAN
VLAN Mapping:	ONU-Based Q-in-Q: 1:1/ N:1 VLAN translation
Spanning Tree:	STP (802.1d), RSTP (802.1w), MSTP (802.1s)
Multicast:	IGMP V2/V1 Snooping & Proxy, MLD V1 Snooping, IGMP Fast leave
Link Aggregation:	LAG/LACP
Forwarding:	IPv4, IPv6
Mirroring:	Port mirroring
Congestion Control	Flow control / Back pressure

Security

DHCP Option:	Option 82 (RFC3046)
PPPoE:	PPPoE+
Protection:	Broadcast / Unknown Multicast / DLF packet limit
PON:	Downstream AES, Rogue ONU/ONT detection, SN, Password. SN+Password Authentication
Access control:	SSH, Packet Filtering (ACL), QoS Policing, User isolation

Quality of Service

Classification:	8 priority queues per GEM port, 802.1p TCI, 802.1q CoS, IPv4 ToS/IP Precedence
Congestion:	Back pressure (802.3x Flow Control)
Scheduling:	SP, WRR, SP+WRR, Egress Traffic Shaping, Rate-limiting

Management

OAM:	Ethernet OAM, FTP/TFTP, ONU Auto-provisioning, ONU Digital diagnostic monitor, Performance Monitoring (PM)
Local:	CLI via CONSOLE/MGMT port
Remote:	SNMP v1/v2c
ONT/ONUs:	Managed over OMCI
Time Sync:	SyncE - ITU-T G.8261/G.8262/G.8264, PTP – IEEE1588V2 & G.8265/G.8275.1/G.8275.2

Power

Power Supply	Dual AC or Dual DC or AC+DC
Power:	320 Watts (Typical).
AC option:	100V to 240V (Pluggable), 50/60 Hz
DC option:	-48VDC (Pluggable)

Physical

Operating Temp:	-20°C to 65 °C
Storage Temp:	-40 °C to 70 °C
Humidity (N.C.):	5 % to 95 % Non-condensing
Rack:	19 inch ANSI/ETSI standard rack
Dimensions:	482.6mm (W) x 286mm (D) x 88.9mm (H)
Weight:	10 kg approx.
Cooling:	Hot-swappable fans,

Regulatory Compliance

Certification:	CE (Conformité Européenne) compliant
EMC Emissions:	CISPR-32:2015 Class A
EMC Immunity:	Radiated RF: EN/IEC61000-4-3: 2006 + A1: 2007 + A2: 2010 level 2
Conducted RF:	EN/IEC61000-4-6: 2013 level 2
Safety:	CE, EN/IEC60950-1/UL60950, UL2043-ready
Laser safety:	IEC60825-1 Class 1 laser safety per G.664
ESD:	EN/IEC61000-4-2: 2008 contact level 2, air discharge level 3
Transient:	EN/IEC61000-4-4: 2012 level 2
Surge:	EN/IEC61000-4-5:2014+A1: 2017 1KV (Line), 2 KV (Earth), 2 KV (Signal)
AC Voltage Dips:	EN61000-4-11: 2004
DC Voltage Dips:	EN61000-4-29
Environment:	EN300019-1-3, QM-333 B2 Category (-5 °C to 50 °C; 50% RH) and QM-333 D Category (-10 °C to 60°C; 50% RH) when in an Outdoor Cabinet
Altitude, Pressure:	GR-63-CORE, IEC 60068-2-13
Drop Test:	GR-63-CORE, IEC 60068-2-31, IEC 60068-2-32
Mechanical:	EN300119-4
Energy:	Broadband Equipment Code of Conduct (2008)
Hazardous	RoHS6, WEEE

** Contact Alphion Sales

The information contained herein is for informational purposes only. Technical claims listed depend on various technical assumptions. Your experience with these products may differ if you operate the products in an environment which is different from the technical assumptions. Alphion reserves the right to modify these specifications without any prior notice. Alphion makes no warranties, expressed or implied, on the contained in this document.

196 Princeton Hightstown Rd,
Princeton Junction,
NJ, 08550 USA
.

P: +1609-936-9001
sales@alphion.com
www.alphion.com