Alphion

Product Brief

AMUX-7208

8-port XGSPON/XGPON & GPON (Co-Existence) OLT

Feature Summary

- 19" standard rack mountable
- Redundant Power
- PON Protection
- Hot-Swappable Modular design for power-supplies and fans.
- 8 XGSPON/XGPON & GPON Combo ports
- Two 100GE QSFP28 uplink ports that can support 8x25GE with "100GE QSFP28 to 8x25GE SFP2B cable" and 4 x 25G/10G SFP+ uplink ports

XG(S)PON & GPON Technology

- Complies with ITU-T G.984.1-5, G.987/G.988, G.9807.1 standards
- XGSPON with 10Gbps(Up)/10Gbps(down), XGPON with 10Gbps(Up)/2.5Gbps(down) & GPON with 2.5Gbps(Up)/1.25Gbps(down) Interfaces
- Supports 5 T-CONT types as per G.984.3 standards
- Supports SN/SN+Password ONU Authentication
- Supports FEC and Rogue ONU detection

Switching and advanced features

- Supports line-speed switching and forwarding capabilities
- Supports 250K MAC address table
- Supports advanced L2 Switching features and VLAN functionality
- Supports IPV4 and IPV6 Multicasting
- Supports time-synchronization using PTP and SyncE
- Supports abundant QOS functions
- Supports advanced security features

Powering

Dual AC/Dual DC redundant power inputs, with pluggable AC and DC inputs modules.



AMUX-7208 with Dual Power supply

Applications

The AMUX-7208 is 1RU Pizza-box GPON platform which supports GPON/XGPON/XGSPON functions and provides End-to-End optical last mile solution with multiple broadband services (Triple-play) to residential and business customers. The high subscriber density and low-cost of entry combined with the operational cost-savings of GPON Technology, makes AMUX-7208 a compelling alternative to legacy last-mile solutions.

Standards

The AMUX-7208 design takes advantages of the latest switching technologies. By complying with the FSAN/ITU-T XGSGPON and GPON standards, the AMUX-7208 achieves interoperability with a wide range of XGSPON and GPON ONTs. With PTP and SyncE support, the AMUX-7208 can be also used in mobile backhaul solutions.

Flexible Provisioning, Management and QOS

The AMUX-7208 supports Telnet/SNMP/CLI for remote management. Its powerful OMCI functions enable remote diagnostics and flexible provisioning of the ONU/ONTs. It's enriched QOS functions such as traffic policy/traffic shaping/rate limit/schedule allows operators to provide flexible bandwidth allocation policy for multiple customized services.

THIS PRODUCT BRIEF IS SUBJECT TO CHANGE AND IS PROVIDED ON AN "AS-IS" BASIS.

SPECIFICATIONS

XG(S)PON/GPON Interface

Ports:	8 XG(S)PON & GPON combo PON ports
Standards:	ITU-T G.984, G.987/G.988, G.9807 compliant
Line rate:	Downstream: 10 Gbps/2.5 Gbps; Upstream: 10 Gbps/2.5 Gbps/1.25 Gbps
Fiber Type:	Single-Mode, BIDI
Transceiver:	Supports N1&B+/N2&C+/E2&D XGSPON Combo transceiver
Split ratio:	1:128 (GPON) and 1:256(XG(S)PON)
Interface Type:	SC/UPC
Tx Power:	3 to 7 dBm(C+), 4 to 8 dBm (N2a)
Rx Sensitivity:	- 30 dBm (C+), -29.5 dBm (N2a)
Rx Overload:	-12 dBm (C+), -9 dBm (N2a)
Wavelength:	GPON - Rx: 1310nm and Tx: 1490nm XG(S)PON - Rx: 1270 nm and Tx:1577nm
T-CONT:	1-5

Ethernet Uplink Trunking Interfaces

100GE/40GE:	2xQSFP28 Ports (Breakout to 8x25GE/10GE with AOC cable).
25GE/10GE:	4xSFP+ ports

Timing Interfaces

SyncE (TODBITS)	1xRJ45 Ethernet port

Management Interfaces

Out-Of-Band	1xRJ45 Ethernet port
Console	1xRJ45 COM port
Alarms	1xRJ45 Ethernet port

Switching

Duplex Switching	
Capacity:	300 Gbps
Throughput:	300 Mpps
VLAN Support:	Port based VLAN, Protocol based VLAN and 801.q VLAN
VLAN Mapping:	ONU-Based Q-in-Q: 1:1/ N:1 VLAN translation
Performance:	300 Mpps throughput, 355K MAC address table.
Spanning Tree:	STP (802.1d), RSTP (802.1w), MSTP (802.1s)
Multicast:	IGMP V1/V2 Snooping & Proxy, MLD V1 Snooping, IGMP Fast leave
Link Aggregation:	LAG/LACP
Forwarding:	IPv4, IPv6
Mirroring:	Port mirroring

Security

DHCP Option:	Option 82 (RFC3046)
PPPoE:	PPPoE+
Protection:	Broadcast / Unknown Multicast / DLF packet limit
PON:	Downstream AES, Rogue ONU/ONT detection, SN, Password. SN+Password Authentication
Access control:	SSH, Packet Filtering (ACL), QoS Policing, User isolation

Quality of Service

Classification:	8 priority queues per GEM port, 802.1p TCI, 802.1q CoS, IPv4 ToS/IP Precedence, Upstream Policing
Congestion:	Back pressure (802.3x Flow Control)
Scheduling:	SP, WRR, SP+WRR, Egress Traffic Shaping

Management

OAM:	Ethernet OAM, FTP/TFTP, ONU Auto-provisioning, ONU Digital diagnostic monitor
Local:	CLI via CONSOLE/MGMT
Remote:	SNMP v1/v2c, Telnet(IPv4/IPv6).
ONT/ONUs:	Managed over OMCI
Time Sync:	SyncE - ITU-T G.8261/G.8262/G.8264, PTP – IEEE1588V2 & G.8265/G.8275.1/G.8275.2

Power

Power Supply	Dual AC or Dual DC or AC+DC
Power:	250 Watts (Typical).
AC option:	100V to 240V, 50/60 Hz, 4A
DC option:	-36VDC to -72VDC

Physical

Operating Temp:	0°C to 50 °C
Storage Temp:	-40 °C to 70 °C
Humidity (N.C.):	10% to 90% Non-condensing
Rack:	19 inch ANSI/ETSI standard rack
Dimensions:	482mm (W) x 286mm (D) x 44 mm (H)
Weight:	4.8kg approx.
Cooling:	Hot-swappable fans,
LED Indicators:	PON/Uplink ports Link Status, RUN status, Alarms (Critical, Major and Minor), Alarm/ Management/Console/TODBITS ports
Buttons:	RESET (Recessed)

Regulatory Compliance

Certification:	CE (Conformité Européenne) compliant
EMC Emissions:	CISPR-32:2015 Class B
EMC Immunity:	Radiated RF: EN/IEC61000-4-3: 2006 + A1: 2007 + A2: 2010 level 2
Conducted RF:	EN/IEC61000-4-6: 2013 level 2
Safety:	CE, EN/IEC60950-1/UL60950, UL2043-ready
Laser safety:	IEC60825-1 Class 1 laser safety per G.664
ESD:	EN/IEC61000-4-2: 2008 contact level 2, air discharge level 3
Transient:	EN/IEC61000-4-4: 2012 level 2
Surge:	EN/IEC61000-4-5:2014+A1: 2017 1KV (Line), 2 KV (Earth), 2 KV (Signal)
AC Voltage Dips:	EN61000-4-11: 2004
DC Voltage Dips:	EN61000-4-29
Environment:	EN300019-1-3, QM-333 B2 Category (-5 °C to 50 °C; 50% RH) and QM-333 D Category (-10 °C to 60°C; 50% RH) when in an Outdoor Cabinet
Altitude, Pressure:	GR-63-CORE, IEC 60068-2-13
Drop Test:	GR-63-CORE, IEC 60068-2-31, IEC 60068-2-32
Mechanical:	EN300119-4
Energy:	Broadband Equipment Code of Conduct (2008)
Hazardous	RoHS6, WEEE

** Contact Alphion Sales

The information contained herein is for informational purposes only. Technical claims listed depend on various technical assumptions. Your experience with these products may differ if you operate the products in an environment which is different from the technical assumptions. Alphion reserves the right to modify these specifications without any prior notice. Alphion makes no warranties, expressed or implied, on the contained in this document.

196 Princeton Hightstown Rd,
Princeton Junction,
NJ, 08550 USA

P: +1609-936-9001
sales@alphion.com
www.alphion.com