Alphion

Product Brief

AMUX-72F0

240-port XG(S)PON & GPON (Co-Existence) OLT

Feature Summary

- 19" standard rack mountable 11RU Chassis
- Redundant DC Power inputs
- Redundant Switch modules (SM), supporting two different types (Type 1 and Type II) with four 25GE/10GE uplink ports on each type
- Uplink cards supporting two different types with two 100GE uplink ports on Type 1 and eight 25GE/10GE/1GE uplink ports on Type II
- Supports 240 GPON/XG(S)PON/Combo-PON ports across 15 Service slots
- Hot-Swappable Modular design for Switch Modules (SM)
- Supports multiple 16-Port GPON Cards, 16-Port XG(S)PON Cards and 8/16 Port Combo-PON line cards across any Service slot
- Class-B PON Protection on XG(S)PON/GPON Ports
- Also supports an Intelligent Computing Card for achieving localized computing for OLTs, and provide edge-oriented intelligent applications and enhanced controlling

XG(S)PON & GPON Technology

- Complies with ITU-T G.984.1-5, G.987/G.988, G.9807 standards
- Supports 10 Gbps/2.5Gbps downstream & 10 Gbps/2.5Gbps/1.25Gbps upstream XG(S)PON/GPON Interfaces
- Supports 5 T-CONT types as per G.984.3 standards
- Supports SN/SN+Password ONU Authentication
- Supports Dynamic Bandwidth Allocation (DBA)
- Supports FEC and Rogue ONU detection

Switching and advanced features

- Supports line-speed switching and forwarding capabilities
- Supports 710K MAC address table
- Supports advanced L2 Switching features and VLAN functionality
- Supports IPv4/IPv6 DHCP Server / DHCP Relay functionality
- Supports IPV4 and IPV6 Multicasting
- Supports time-synchronization using 1588V2 PTP
- Supports abundant QOS functions
- Supports advanced security features

Powering

Dual DC redundant power inputs (pluggable)

Applications

The AMUX-72F0 is an 11RU Chassis based hybrid platform which supports next next-generation converged PON technology. AMUX-72F0 provides GPON, XG-PON, XGS-PON, Combo-PON access and 100GE/25GE/10GE/GE uplinks. The device can be deployed in FTTH, FTTB, FTTC, FTTD, FTTM scenarios to provide service for residential subscribers, business customers, mobile and fixed backhauling, Wi-Fi hotspot backhaul, etc.

With 1588V2 PTP support, the AMUX-72F0 can be also used in mobile backhaul solutions. By supporting 1588V2 synchronization without extra clock equipment it saves investment for FTTM application. The AMUX-72F0 gets external 1588V2 signals and transfers to the connected ONTs through OMCI. ONT then transfers 1588V2 signals to 4G/5G station or small cell.

Standards

The AMUX-72F0 design takes advantages of the latest switching technologies. By complying with the FSAN/ITU-T XG(S)PON and GPON standards, the AMUX-72F0 achieves interoperability with a wide range of XG(S)PON and GPON ONTs.

Flexible Provisioning, Management and QoS

The AMUX-72F0 supports Telnet/SNMP/CLI for remote management. Its powerful OMCI functions enable remote diagnostics and flexible provisioning of the ONU/ONTs. It's enriched QOS functions such as traffic policy/traffic shaping/rate limit/schedule allows operators to provide flexible bandwidth allocation policy for multiple customized services.

THIS PRODUCT BRIEF IS SUBJECT TO CHANGE AND IS PROVIDED ON AN "AS-IS" BASIS.

SPECIFICATIONS

XG(S)PON/GPON Interface

Ports:	240 XG(S)PON & GPON combo PON ports
Standards:	ITU-T G.984, G.987/G.988, G.9807 compliant
Line rate:	GPON: 1.25Gbps (Upstream), 2.5Gbps (Downstream) XGPON: 2.5Gbps (Upstream), 10Gbps (Downstream) XGSPON: 10Gbps (Upstream), 10Gbps (Downstream)
Fiber Type:	Single-Mode, BIDI
Transceiver:	Supports B+/C+(GPON) and N1&B+/N2&C+/E2&D XG(S)PON&GPON Combo transceivers
Split ratio:	1:64 (GPON) and 1:128 (XG(S)PON)
Interface Type:	SC/UPC
Tx Power:	3~7dBm (C+), 4~8dBm (N2a)
Rx Sensitivity:	-30 dBm (C+), -29.5dBm (N2a)
Rx Overload:	-12 dBm (C+), -9dBm (N2a)
Wavelength:	GPON - Rx: 1310nm and Tx: 1490nm XG(S)PON - Rx: 1270 nm and Tx:1577nm
T-CONT:	1-5

Ethernet Uplink Trunking Interfaces

25GE/10GE:	4xQSFP/SFP+ Ports per SM card (Type I or Type II)
25GE/10GE/GE	8xQSFP/SFP+/SFP Ports per Uplink Card Type1
100GE	2xQSF28 Ports per Uplink Card Type II

Management Interfaces

Out-Of-Band	1xRJ45 Ethernet port
Console	1xRJ45 COM port

Switching

Switching Capacity	7.2Tbps (Type 1 SM) or 3.8Tbps (Type II SM)
Per Slot: Bandwidth:	200 Gbps
VLAN Support:	Port based VLAN, Protocol based VLAN and 801.q VLAN
VLAN Mapping:	ONU-Based Q-in-Q: 1:1/ N:1 VLAN translation
Spanning Tree:	STP (802.1d), RSTP (802.1w), MSTP (802.1s)
Multicast:	IGMP V2/V1 Snooping & Proxy, MLD V1 Snooping, IGMP Fast leave
Link Aggregation:	LAG/LACP
Forwarding:	IPv4, IPv6
Mirroring:	Port mirroring
Congestion Control	Flow control / Back pressure

Security

DHCP Option:	Option 82 (RFC3046)
PPPoE:	PPPoE+
Protection:	Broadcast / Unknown Multicast / DLF packet limit
PON:	Downstream AES, Rogue ONU/ONT detection, SN, Password. SN+Password Authentication
Access control:	SSH, Packet Filtering (ACL), QoS Policing, User isolation

Quality of Service

Classification:	8 priority queues per GEM port, 802.1p TCI, 802.1q CoS, IPv4 ToS/IP Precedence
Congestion:	Back pressure (802.3x Flow Control)
Scheduling:	SP, WRR, SP+WRR, Egress Traffic Shaping, Rate-limiting

Management

OAM:	Ethernet OAM, FTP/TFTP, ONU Auto-provisioning, ONU Digital diagnostic monitor, Performance Monitoring(PM)
Local:	CLI via CONSOLE/MGMT port
Remote:	SNMP v1/v2c
ONT/ONUs:	Managed over OMCI
Time Sync:	PTP - IEEE1588V2

Power

Power Supply:	Dual DC (Pluggable), -40V DC to -60V DC input
Power:	1143 Watts (Typical)

Physical

Operating Temp:	0°C to 50 °C
Storage Temp:	-40 °C to 70 °C
Operating RH:	10% to 90% Non-condensing
Storage RH:	5% to 95% Non-condensing
Rack:	19 inch ANSI/ETSI standard rack
Dimensions:	482.6mm (W) x 286mm (D) x 488mm (H)
Weight:	Fully loaded: 44 kg, Chassis only: 18.5 kg
Cooling:	Fan Tray

Regulatory Compliance

Certification:	CE (Conformité Européenne) compliant
EMC Emissions:	CISPR-32:2015 Class A
EMC Immunity:	Radiated RF: EN/IEC61000-4-3: 2006 + A1: 2007 + A2: 2010 level 2
Conducted RF:	EN/IEC61000-4-6: 2013 level 2
Safety:	CE, EN/IEC60950-1/UL60950, UL2043-ready
Laser safety:	IEC60825-1 Class 1 laser safety per G.664
ESD:	EN/IEC61000-4-2: 2008 contact level 2, air discharge level 3
Transient:	EN/IEC61000-4-4: 2012 level 2
Surge:	EN/IEC61000-4-5:2014+A1: 2017 1KV (Line), 2 KV (Earth), 2 KV (Signal)
DC Voltage Dips:	EN61000-4-29
Environment:	EN300019-1-3, QM-333 B2 Category (-5 °C to 50 °C; 50% RH) and QM-333 D Category (-10 °C to 60°C; 50% RH) when in an Outdoor Cabinet
Altitude, Pressure:	GR-63-CORE, IEC 60068-2-13
Drop Test:	GR-63-CORE, IEC 60068-2-31, IEC 60068-2-32
Mechanical:	EN300119-4
Energy:	Broadband Equipment Code of Conduct (2008)
Hazardous	RoHS6, WEEE

** Contact Alphion Sales

The information contained herein is for informational purposes only. Technical claims listed depend on various technical assumptions. Your experience with these products may differ if you operate the products in an environment which is different from the technical assumptions. Alphion reserves the right to modify these specifications without any prior notice. Alphion makes no warranties, expressed or implied, on the contained in this document.

196 Princeton Hightstown Rd,
Princeton Junction,
NJ, 08550 USA

P: +1609-936-9001
sales@alphion.com
www.alphion.com